

## **AQUARIUS PUMP COMPANY**

2C

## AVAILABLE MOUNTING CONFIGURATIONS

2C-VM VERTICAL CLOSE COUPLED

OPERATING LEVELS		
MIN FLOW	20 GPM	4.54 m <sup>3</sup> /h
MAX FLOW	160 GPM	36.3 m <sup>3</sup> /h
DISCHARGE SIZE	2"	51 mm
SUCTION SIZE	2.5"	64 mm
MAX SPEED	3525 RPM	3525 RPM
SHUT-OFF HEAD	80'	24.4 m
BEP HEAD	72'	22 m
BEP FLOW	120 GPM	27.3 m <sup>3</sup> /h
BEP	81%	81%

PARTS	STANDARD MATERIAL (ALL IRON)	
VOLUTE	CASTIRON	
IMPELLER	CASTIRON	
MECHANICAL SEAL	T-21 SINGLE CARBON-CERAMIC WITH BUNA O-RING SEAT AND STAINLESS STEEL METAL PARTS	
MOTOR	TEFC WASHDOWN-DUTY (IP55) W/ DRIP CAP	

- Ideally suited for OEM booster applications
- Back pull-out design
- Heavy duty cast iron construction
- Off the shelf availability from various locations
- Two-year factory warranty
- Rotating assembly retrofits into most competitors'
- Performance meets or exceeds competition
- "Shower curtain shield" motor moisture protection
- Motor built to Aquarius's specifications



A typical picture of the pump is shown. Please contact Aquarius Pump Company forfurther details. All information is approximate and for general guidance only.

The 2C Edge End Gun Booster pump is designed with Aquarius's renowned quality and durability. It features a 2"discharge, 2.5" suction, and enclosed impeller. Aquarius's patented Cycloseal® design is standard.

- Motor thermostat Auto reset
- Weight: 70 lbs.
- Better moisture protection
- Improved motor bearing protection
- Sealed conduit box and shaft ends
- Meets IP55 standards
- Epoxy-coated rotor
- Double dipped and baked motor windings
- Premium efficiency
























## **AQUARIUS PUMP COMPANY**

2C

