



AQUARIUS PUMP COMPANY

4409T

AVAILABLE MOUNTING CONFIGURATIONS

4409T-EM ENGINE MOUNT

OPERATING LEVELS

MIN FLOW	220 GPM	50 m ³ /h
MAX FLOW	1000 GPM	227 m ³ /h
DISCHARGE SIZE	4"	102 mm
SUCTION SIZE	4"	102 mm
SOLIDS HANDLING	2.38"	60 mm
MAX SPEED	2200 RPM	2200 RPM
SHUT-OFF HEAD	136'	41 m
BEP HEAD	88'	27 m
BEP FLOW	750 GPM	170 m ³ /h
BEP PERCENT	73%	73%



A typical picture of the pump is shown. Please contact Aquarius Pump Company for further details. All information is approximate and for general guidance only.

PARTS	STANDARD MATERIAL (ALL IRON)
IMPELLER	DUCTILE IRON
VOLUTE	DUCTILE IRON
SHAFT	17-4 SS
SHAFT SLEEVE	303 SS
SUCTION COVER	DUCTILE IRON
SEAL HOUSING	DUCTILE IRON
MECHANICAL SEAL	SILICON CARBIDE X SILICON CARBIDE
BEARING FRAME	DUCTILE IRON

The 4409T pump is designed with Aquarius's renowned quality and durability. It features a 4" discharge, 4" suction, and enclosed impeller. Aquarius's patented Cycloseal® design is standard, with a Type 2 single mechanical seal with Buna-N elastomers, stainless steel hardware and silicon carbide vs. silicon carbide seal faces for abrasion resistance.

- Low cost, durable Aquarius Quality
- Completely re-buildable
- Redi-Prime® available for fully-automatic continuous priming
- Also available with Venturi Prime option
- Competitive Pricing



AGRICULTURE



FOOD



INDUSTRIAL



MINING



MUNICIPAL



OIL & GAS



REFRIGERATION



RENTAL




AQUARIUS PUMP COMPANY

4409T

Performances shown are for S.G. 1.0
80°F water, frame mount configuration.
Other mounting styles or S.G.
may require curve adjustments.

Speed	Impeller Dia.	Style	Volute	Solids Dia.	N _s	Suction	Discharge	No. Vanes
VARIOUS	8.75"	ENCLOSED	SINGLE	2.38"	2150	4"	4"	2



Aquarius Pump Company	01	01/05/16	BE	MODEL : 4409T	CURVE NO. 4409TVA
	00	06/25/15	BE	TYPE : SOLIDS HANDLING	